

ACCESS CONTROL SYSTEMS



PN-6750 PROXIMITY SENSOR AND NUMERIC KEYPAD WITH LCD

- Stand-alone Access Controller
- Access Mode :
 - Card Only
 - Card with PIN Code (4 digits)
- Capacity : 3,000 Proximity Cards
- PIN Code : 5 programmable PIN Codes (4 digits)
- Read Range : 5 ~ 10 cm
- Programmable door release time from 1 to 98 seconds
- Non-volatile memory for 10 years data retention without any battery backup
- ABS-Plastic case with plastic keypad
- DC 12V
- 140 (H) x 86 (W) x 29 (D) mm



PUA-310 PROXIMITY SENSOR

- Secondary Access Controller
- Used as Door Exit Proximity Reader
- Read Range: 5 ~ 10 cm
- ABS-Plastic case with plastic keypad
- DC 12V
- 116 (L) x 73 (W) x 13 (H) mm

* Note : Acts as slave proximity reader.
Requires attachment to PP-3750 main access controller to function properly.



PROXIMITY CARD / KEYTAG

Thick Proximity Card

- 125 KHz Passive Type
- 54 (W) x 85 (L) x 1.8 (H) mm

Thin Proximity Card

- Printable
- 125 KHz Passive Type
- 54 (W) x 85 (L) x 0.8 (H) mm

Proximity Keytag

- 125 KHz Passive Type
- 30.4 (W) x 45.3 (L) x 8.7 (H) mm




ELECTROMAGNETIC LOCK

- Holding Force : 250 kgs
- DC 12V
- 250 (L) x 42.5 (W) x 37 (H) mm




ELECTRIC BOLT


- With Door Position Sensor
- DC 12V
- 205 (L) x 38 (W) x 44 (H) mm




EBOLT BOLT HOUSING




EBOLT BOLT PLATE HOUSING



Z - BRACKET



U - BRACKET



L - BRACKET



KEY SWITCH (OVERRIDE KEY)