



BEST USED WITH
125-250 MICRONS

A4

Hot & Cold
LAMINATION

LAMINATING MACHINE

JLM02-220(A4)



FEATURES:

- ✓ Heavy-duty
- ✓ Ideal for home and office use
- ✓ Easy and convenient to use
- ✓ Power ready and preheating light
- ✓ Raise temperature smoothly
- ✓ Keep temperature steadily
With temperature control knob and temperature meter
- ✓ Excellent sealing quality
- ✓ With reverse switch

Parts and Description



Specifications

Voltage:	220V/50/Hz
Max. Pouch Capacity:	250 microns per pouch
Power:	600W
Laminating Speed:	660mm/min
Max. Laminating Width:	220mm
Operating Temp.:	100-200 °C
Preheat Time:	3-5min
Weight:	6.5kg

Ideal Laminating Temperature:

Thickness	Heat Temperature
125 mic (0.125mm)	130 - 140 °C
250 mic (0.25mm)	180 - 190 °C



LAMINATING IS IDEAL FOR:
Protecting and preserving print and documents
Articles such as: computer prints, photographs,
paper cuttings, business cards, labels, poster
and many more

Excellent Invention

NOTE:

If the pouch adhesive is still cloudy, the laminating temperature is too low. If the material shows bubbles in the adhesive or a wavy irregular surface, the temperature is too high. In either case, adjust the heat setting and wait for a few minutes for the equipment to reach the new temperature.

* The design and specifications are subject to change without prior notice.
* Actual unit may vary from the picture shown in this flyer



On Parts & Service