



















CCTV

PROFESSIONAL SURVEILLANCE AND
SECURITY EQUIPMENT

 **INFINITE**
SYSTEMS TECHNOLOGY CORP.
www.infinitesystems.net

7/F Cityland 10 Tower 1, #156 H.V. Dela Costa Street, Ayala Avenue, Makati City
Tel Nos: +63 (02) 892-9073 to 77 | Fax No.: +63 (02) 892-9077 | E-mail: sales@infinite.com.ph

MODEL	IMAGE SENSOR	RESOLUTION	LENS	INFRARED LEDS	VIEW ANGLE	POWER REQUIREMENT	DIMENSION
INDOOR CAMERAS							
ARC25 COLOR DOME CAMERA WITH IR	 1/4" Sony CCD Sensor	420 TV Lines	3.6mm Board Lens	30 IR LED	45°-90° View Angle	DC 12V	94(D) x 73(H)mm
RS3422 COLOR DOME CAMERA	 1/3" Sharp CCD Sensor	420 TV Lines	3.6mm Board Lens	--	45°-90° View Angle	DC 12V	105(D) x 77(H)mm
RK3422 COLOR DOME CAMERA WITH IR	 1/3" Sony CCD Sensor	420 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	92(D) x 77(H)mm
RC3422 METAL DOME CAMERA	 1/3" Sony CCD Sensor	420 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	92(D) x 77(H)mm
RK3542 COLOR DOME CAMERA WITH IR	 1/3" Sony CCD Sensor	540 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	92(D) x 77(H)mm
RC3542 METAL DOME CAMERA	 1/3" Sony CCD Sensor	540 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	92(D) x 77(H)mm
RK3652 COLOR DOME CAMERA WITH IR	 1/3" Sony CCD Sensor	650 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	92(D) x 77(H)mm
RK3702 COLOR DOME CAMERA WITH IR	 1/3" Sony CCD Sensor	700 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	92(D) x 77(H)mm
V3422 ELEVATOR CAMERA	 1/3" Sony CCD Sensor	420 TV Lines	2.9mm Board Lens	--	110° View Angle	DC 12V	105(D) x 60(H)mm
HIDDEN CAMERAS							
L4422 MINIATURE CAMERA	 1/4" Sharp CCD Sensor	420 TV Lines	2.9mm Board Lens	--	110° View Angle	DC 12V	39(W) x 39(H) x 21(D)mm
LSDCS SMOKE DETECTOR CAMERA	 1/3" Sony CCD Sensor	420 TV Lines	3.6mm Board Lens	--	110° View Angle	DC 12V	119(D) x 56(H) mm
LPRCS PIR CAMERA	 1/3" Sony CCD Sensor	420 TV Lines	3.7mm Toper Pinhole Lens	--	45°-90° View Angle	DC 12V	70(W) x 40(H) x 119(D)mm
OUTDOOR CAMERAS							
ARC20 COLOR OUTDOOR CAMERA WITH IR	 1/4" Sharp CCD Sensor	420 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	80(D) x 165(H)mm
BB3422 COLOR OUTDOOR CAMERA WITH IR	 1/3" Sony CCD Sensor	420 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	55(D) x 95(H)mm
BB3482 COLOR OUTDOOR CAMERA WITH IR	 1/3" Sony CCD Sensor	480 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	55(D) x 95(H)mm
BB3542 COLOR OUTDOOR CAMERA WITH IR	 1/3" Sony CCD Sensor	540 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	55(D) x 95(H)mm
BC3542 COLOR OUTDOOR CAMERA WITH IR	 1/3" Sony CCD Sensor	540 TV Lines	3.6mm Board Lens	36 IR LED	45°-90° View Angle	DC 12V	228(W) x 97(H) x 82(D)mm
BA3702 COLOR OUTDOOR CAMERA WITH IR	 1/3" Sony CCD Sensor	700 TV Lines	3.6mm Board Lens	24 IR LED	45°-90° View Angle	DC 12V	295(W) x 120(H) x 103(D)mm

CCTV


PROFESSIONAL SURVEILLANCE AND SECURITY EQUIPMENT

MODEL	IMAGE SENSOR	RESOLUTION	LENS	INFRARED LEDS	VIEW ANGLE	POWER REQUIREMENT	DIMENSION
-------	--------------	------------	------	---------------	------------	-------------------	-----------

LONGRANGE CAMERAS

LIT90 LONG-RANGE OUTDOOR CAMERA W/ IR		1/3" Sony CCD Sensor	420 TV Lines	4-9mm Manual Varifocal Lens	36 IR LED	45°-90° View Angle	DC 12V	80(D) x 165(H)mm
BF3542 LONG-RANGE OUTDOOR CAMERA W/ IR		1/3" Sony CCD Sensor	540 TV Lines	4-9mm Auto-Iris Varifocal Lens	56 IR LED	45°-90° View Angle	DC 12V	80(D) x 165(H)mm
ARC50-700 LONG-RANGE OUTDOOR CAMERA W/ IR		1/3" Sony CCD Sensor	700 TV Lines	2.8-12mm Manual Varifocal Lens	36 IR LED	45°-90° View Angle	DC 12V	80(D) x 165(H)mm
BD3702 LONG-RANGE OUTDOOR CAMERA W/ IR		1/3" Sony CCD Sensor	700 TV Lines	4-9mm Manual Varifocal Lens	36 IR LED	45°-90° View Angle	DC 12V	80(D) x 165(H)mm

SQUARE CAMERA




S3422 COLOR SQUARE CAMERA		1/3" Sony CCD Sensor	420 TV Lines	C/CS Mount Lens	--	45°-90° View Angle	DC 12V	105(L) x 62.5(W) x 62.5(H)mm
-------------------------------------	---	-------------------------	--------------	-----------------	----	--------------------	--------	---------------------------------

SQUARE CAMERA ACCESSORIES/ POWER SUPPLY

MODEL	DESCRIPTION	MODEL	DESCRIPTION	MODEL	DESCRIPTION	MODEL	DESCRIPTION	MODEL	DESCRIPTION
EP-25FL	WIDE ANGLE LENS	EP-4FL	STANDARD ANGLE LENS	EP-MZ	MANUAL ZOOM LENS	EP-4M	AUTO-IRIS LENS	HOUSING	
	2.5mm Fixed-Iris Lens 120° View Angle		4mm Fixed-Iris Lens 76.2° View Angle		6-15mm Adjustable Lens 44-19° View Angle		4mm Auto-Iris Lens 76.2° View Angle		Aluminum Housing for Outdoor Camera
BRACKET-S	Aluminum Bracket for Small Camera	BRACKET-L	Aluminum Bracket for Large Housing	ADAPTOR-500MA	Regulated DC Power Supply	PS-3000MA	Regulated DC Power Supply (12VDC, 3000MA)	AVR500W	Automatic Voltage Regulator with Power-ON delay


MODEL	IMAGE SENSOR	RESOLUTION	PAN/TILT RANGE	MANUAL SPEED PAN/TILT	PRESET POINT/ SPEED/ ACCURACY	AUTO SCAN	TEMP/ COMM.	POWER SUPPLY	IR LEADS	IN/ OUT DOOR
-------	--------------	------------	----------------	-----------------------	-------------------------------	-----------	-------------	--------------	----------	--------------

SPEED DOME CAMERA

SPDZ SPEED DOME CAMERA WITH ZOOM		Hitachi 22 x zoom	520 TV Lines	360° Continue; 0~90° Flip	0.1 ~ 300°/sec.; 0.1~120°/sec.	128 ; 400° /sec. ; ± 0.10°	Highly efficient 3-dimension scan Continue Manual	-220°C~60°C; RS485 control	24VCA	N/A	In/out door
SPDZ-MINI MINI SPEED DOME CAMERA WITH ZOOM		Hitachi 10 x zoom	520 TV Lines	360° Continue; 0~90° Flip	0.1 ~ 240°/sec. ; 0.1~120°/sec.	128 ; 300° /sec. ; ± 0.10°	Home position Continue Manual	-30°C~70°C; RS485 control	24VCA	N/A	In/out door
SPD-MINI MINI SPEED DOME CAMERA WITHOUT ZOOM		1/3" Sony CCD Sensor w/ IR	420 TV Lines	360° Continue 0~90° Flip	Max. 50°/sec. ;	16 -- --	Continue Manual	-30°C~65°C; RS485 control	24VDC	24 pcs. ; 20M	Indoor

MODEL	PAN/TILT CONTROLLER	SET POINTS & CRUISE TRACKS	TYPE OF CONTROLLER	COMM	BAUD RATE	COMM DISTANCE	DIMENSION	WEIGHT
-------	---------------------	----------------------------	--------------------	------	-----------	---------------	-----------	--------

CTL SPEED DOME CONTROLLER		Controller with 3D joystick (Pan/Tilt, Zoom)	Set or call the set points and cruise tracks	Manual / Automatic	RS-485/RS-232 (PC)	2400-19200 Bps	Max. 1200m	95 (H) X 205 (L) X 205 (W)	1.5Kg
--	---	--	--	-----------------------	-----------------------	-------------------	------------	-------------------------------	-------

MODEL	OUTPUT	COMPRESSION FORMAT	NETWORK	REAL TIME	ASSUMPTIONS
TDVR08 8-CHANNELS		8-channel PC DVR	MPEG 4	with NETWORK (or Remote Monitoring)	with Real Time
TDVR16 16-CHANNELS		16-channel PC DVR	MPEG 4	with NETWORK (or Remote Monitoring)	with Real Time

Clients should have DSL Connection with Public IP Address, Router, Router Password in order for Remote Monitoring to work

CCTV

PROFESSIONAL SURVEILLANCE AND SECURITY EQUIPMENT

MODEL	OUTPUT	COMPRESSION FORMAT	NETWORK	REAL TIME
DIGITAL VIDEO RECORDER				
HDVR08 8-CHANNELS	8-channel PC DVR	H.264	with NETWORK (or Remote Monitoring)	with Real Time
HDVR16 16-CHANNELS	16-channel PC DVR	H.264	with NETWORK (or Remote Monitoring)	with Real Time

ASSUMPTIONS

Clients should have DSL Connection with Public IP Address, Router, Router Password in order for Remote Monitoring to work

MODEL	NETWORK	COMPRESSION FORMAT	HARD DISK	BACK UP	MOBILE DEVICE VIEWING SUPPORT
DVR04-NETWORK STANDALONE DVR 4 CHANNELS	with Network	H.264 Compression	SATA Hard disk interface (hard disk sold separately)	USB Flash Drive Port	Apple ipad/ iphone, Android
DVR08-NETWORK STANDALONE DVR 8 CHANNELS	with Network	H.264 Compression	SATA Hard disk interface (hard disk sold separately)	USB Flash Drive Port	Apple ipad/ iphone, Android
DVR16-NETWORK CIF STANDALONE DVR 16 CHANNELS	with Network	H.264 Compression	SATA Hard disk interface (hard disk sold separately)	USB Flash Drive Port	Apple ipad/ iphone, Android
DVR16-NETWORK STANDALONE DVR 16 CHANNELS	with Network	H.264 Compression	SATA Hard disk interface (hard disk sold separately)	USB Flash Drive Port	Apple ipad/ iphone, Android
DVR16-NETWORK-D1 STANDALONE DVR 16 CHANNELS	with Network	H.264 Compression	SATA Hard disk interface (hard disk sold separately)	USB Flash Drive Port	Apple ipad/ iphone, Android

REMOTE MONITORING REQUIREMENTS: 1.) Public IP DSL connection 2.) Routers and Router Passwords 3.) Laptop/PC where remote viewing will be performed

MODEL	DESCRIPTION	FRAME RATE	COMPRESSION	MODEL	DESCRIPTION	FRAME RATE	COMPRESSION
DVR CARDS				DVR CARDS			
SK2000F	4-Channel DVR card	30	MPEG 4 Compression	DS-6808A	8-Channel DVR card	120	H.264 Compression
VC8000	8-Channel DVR card	120	MPEG 4 Compression	TE-8008E	8-Channel DVR card	120	H.264 Compression

NOTE: If client is requiring installation, client is required to avail of commissioning of CCTV Equipments

MODEL	DESCRIPTION	MODEL	DESCRIPTION
HARD DISK		MONITOR	
HDISK500	500GB Hard disk (SATA Interface)	LCD MONITOR	15" VGA MONITOR (for DVR Computer Sys.)
HDISK1TB	1TB Hard disk (SATA Interface)	LCD MONITOR	18.5" VGA MONITOR (for DVR Computer Sys.)
HDISK2TB	2TB Hard disk (SATA Interface)	LCD MONITOR	20" VGA MONITOR (for DVR Computer Sys.)

MODEL / DESCRIPTION

MISCELLANEOUS ITEMS

					
DVR-OPTI	D.I.Y. CABLE	POWER STRIP	BALUN	ACTIVE BALUN	VGA BALUN
Optical Media Back-up Device	Coaxial CCTV Cable w/Power (available in 20, 30, 40 & 60m)	6-Pocket Power Strip	CCTV BALUN for UTP Cabling	CCTV Video Signal Amplifier for UTP Cabling	VGA Balun
					
FS-4616SR	FS-4504SR	BNCCON	GROUND LOOP ISOLATOR	VIDEO SPLITTER	VGA SPLITTER
16-Channel CCTV Balun	4-Channel CCTV Balun	BNC Connector	Interference Filter for CCTV Video Signal	Video Signal Splitter	Computer VGA Signal Splitter